



Experiencing Staining or Odor?

The Exeterline™ EIFA Iron Filter Is the Solution!

The Exeterline™ EIFA units oxidize and filter sulfur odor (hydrogen sulfide gas), iron and manganese



Benefits of Iron / Odor Free Water:

- Filtering iron will prevent buildup in plumbing fixtures, piping, water heaters and all other appliances saving you money in the long run
- Filtering iron and manganese will prevent reddish brown or black staining in the bathroom and kitchen accessories
- No more rotten egg sulfur smell when running the shower or faucet

Standard Equipment Includes:

- A purple/grey media called Greensand Plus is used for removing soluble iron, manganese and hydrogen sulfide gas from well water
- Vortech™ style tank conserves natural resources by eliminating the use of gravel support beds and lowering the required backwash time and flow rate, saving you money by conserving water
- Full 1" Internal Piping
- 10"X 16" blue pot perm tank
- Reliable automatic backwashing control valve, capable of being custom tailored to your specific application
- All accessories for installing the EIFA unit and pot perm tank

Removal Process:

- The Exeterline EIFA filter oxidizes and filters hydrogen sulfide gas (odor), iron and manganese by using a potassium permanganate solution to regenerate the Greensand Plus with oxygen

Application Benefits:

- Greensand Plus eliminates iron, manganese, and hydrogen sulfide gas
- Standard EIFA units are programmed on a 12-day timer, and are set to regenerate on the day and time of your choice
- Filters down to 20 – 40 micron

Required Conditions:

- Influent water must not be corrosive
- For corrosive conditions, Exeterline EA models
- Cubic foot capacities at 1ppm:
Iron alone 10,000 gallons
Iron and Manganese 7,000 gallons
Hydrogen Sulfide Gas 3,000 gallons
- Batch regenerate before total exhaustion with 2-4 oz. of Pot Perm per cubic foot of media

Dimensions:

Model	A	B	C	D
10EIFA	55	9	48	49.25
15EIFA	61	10	54	55.25
20EIFA	59	12	52	53.25
25EIFA	61	13	54	55.25

A= Overall height in inches

B= Tank diameter in inches

C= Tank height in inches

D= Inlet height in inches (specify 0.75" or 1" Bypass, or 1.25" Yoke)

* May Require Application Engineering

* New, Coming 2009



Specifications:

Model	Mineral Volume (Ft. ³)	Peak Flow (GPM)	Backwash Rate (GPM)	Shipping Weight (Lbs)
10EIFA	1	5.0	5.0	110
15EIFA	1.5	7.0	5.0	160
20EIFA	2	12.0	8.0	210
25EIFA	2.5	15.0	10.0	260

Copyright REPCO July 2008