



REPCO
Since 1954



REPCO
Engineering



REPCO
Distributing



REPCO
Manufacturing



Got Hard Water?

The REPCO 5R Water Softener Is the Solution!

The REPCO 5R Softener removes Hardness, Iron and Manganese

Benefits of Having Soft Water:

- Prevention of scale will result in longer lasting plumbing fixtures and appliances including your water heater and dishwasher, lasting up to 1/3 longer
- Hot water heater efficiency will increase by up to 29%
- Softer Hair and Skin
- Cleaner, brighter and longer lasting clothes
- Less soap scum buildup in the bathroom and kitchen

Standard Equipment Includes:

- High Capacity Ion Exchange Resin Media
- Vortech™ style tank conserves natural resources by eliminating the use of gravel support beds and lowering the required backwash time and flow rate, saving you money by conserving water
- Full 1" Internal Piping
- 18"x33" Brine Tank
- Twin motor automatic backwashing control valve, capable of being custom tailored to your specific application.
- All accessories for installing the 5R unit and brine tank

Removal Process:

- A soft sodium or potassium ion is used to remove hard water ions of calcium and magnesium scale, as well as the staining ions of iron and manganese

Application Options:

- 5 ppm removal of iron and manganese (must be in solution)
- Standard 5R units are programmed on a 12-day timer, and are set to regenerate on the day and time of your choice
- Metered 5R units are set to regenerate upon water consumption which offers environmental and economical use of sodium or potassium

Required Conditions:

- Total iron and manganese must be less than 5 ppm
- Iron and manganese must be in solution (clear)
- 5R softeners are not filters. If a filter is required, refer to one of many REPCO filters



Dimensions:

Model	A	B	C	D
5R30-2	56	9	48	49.75
5R45-2	62	10	54	55.75
5R60-2	60	12	52	53.75
5R90-2	73	14	65	66.75
5R120-2	73	16	65	66.75

A= Overall height in inches

B= Tank diameter in inches

C= Tank height in inches

D= Inlet height in inches (specify 0.75" or 1" Bypass, or 1.25" Yoke)



Specifications:

Model	Mineral Volume (Ft. ³)	Peak Flow (GPM)	Backwash Rate (GPM)	Shipping Weight (Lbs)
5R30-2	1	7	2.0	90
5R45-2	1.5	9	2.4	120
5R60-2	2	14	3.5	160
5R90-2	3	14-25	4	210
5R120-2	4	14-25	5	260

Copyright REPCO June 2008